



FLOOR PLAN

SCALE : 1/4" = 1'-0"

J. K. ...
7-21-98

INTERIOR FINISHES
TO COMPLY WITH
SECTION 3708 SFG

9/2/98

8" TYPE "X" BOTH SIDES

STUDS "O.C.

HOURS PER JAMB

BEL MTL. QUIRED

LABEL SCHEDULE

AR

D
PRECAST PANELS AND STRIPS BETWEEN

NS:
0. FT.
0. FT.
0. FT.

UNPROTECTED SPANCY

X. AREA EXTINGUISHING 11.3 (E)

ADJACENT TENANT SPACE

EXISTING ADJACENT TENANT SPACE

EXISTING 1-HR. FIRE RATED WALL SEE SUITE LOCATION PLAN FOR INDIVIDUAL SUITE REQUIRED FIRE RATING FOR 1-HR FIRE RATED WALLS SEE DETAIL 1/A-2

EXISTING 1-HR. FIRE RATED WALL SEE SUITE LOCATION PLAN FOR INDIVIDUAL SUITE REQUIRED FIRE RATING FOR 1-HR FIRE RATED WALLS SEE DETAIL 1/A-2

PROVIDE 1"x2" FURRING STRIPS OVER EXISTING CONCRETE TILT WALL PNL. W/ R-3 INSULATION BETWEEN W/ 1/2" DRYWALL OVER

1/4" CLEAR TEMPERED FIXED GLASS (6'-0" X 4'-0") WOOD FRAME, PAINTED

PROVIDE R-11 BATT INSUL IN NEW WALL