SECURITY GRILL TO REMAIN

12 RISERS @ 8" EA. = 8'-0"
11 TREADS @ 9" EA. = 10'-0"

3/A201

LVL BEAM

5.25"x11.25" LVL HDR.

EX 3x12@16" O.C.

EXISTING RESIDENTIAL TENANT BOILERS AND HOT WATER HEATERS.

EX 6" X 6" WOOD GIRDER

EX 4" SQ STEEL POST EVERY 7'-0" O.C. TYPICAL.

EX 4x12@16" O.C.

EXISTING MECHANICAL EQUIP. (N.I.C.)

36"x80" S.C.

TRASH

P8

P7

QUARRY TILE FLOORING.

CONV. OVENS

+/- 3'-8"

+/- 12'-9"

37'-0" +/-

FOOD PREP/STORAGE

P2

EXISTING STAIR (NO WORK)

UP

(D)

96" x 96" W.I. REF.

96" x 96" W.I. FRZ.

32"x80" S.C.

NEW RES. ELEC. METERS. WORK FILED UNDER SEPARATE APPLICATION.

SPRINKLER + ELECTRICAL EQUIPMENT ROOM

MAIN DIS-CONNECT+ METER-COM. SPACE

NEW WATER METER

EXISTING SPRINKLER MAIN, OS+Y VALVE

SERVICE ENTRY

7'-1"

4'-0"

34"x80" S.C.

DN

P2

P7

P3

P

FRYER

Q

60" RANGE 24" GRIDDLE (2) OVENS

2'-0½"

EP-1 COM. SPACE

3'-0"

2'-0"

+/-2'-9"

2'-1"

2'-0"

3'-3"

2'-6"

EXIT

EXISTING AIR SHAFT

+/-5'-10" V.I.F.

3'-0"

1'-2"

3'-0"

1'-2½"

BLENDERS

FOOD PREP

P3

P2

RICE

8'-5"

3'-2"

11'-2"

2½"

POS/PICK-UP

SNEEZE GUARD

P5

TOILET RM.

P6

32"x80" S.C.

ADA TOILET RM.

8'-0"

34"x80" S.C.

BEVERAGE

TRASH/ RECYCLE

CONDIMENTS

REACH-IN CASE

DINING

RESIDENTIAL STAIR (N.I.C.)

RESIDENTIAL ENTRY (N.I.C.)

EXISTING FLOOR OPENING TO BE CLOSED WITH 1 HR RATED FLOOR CONSTRUCTION: 2x10 JOISTS 16" O.C., 2x10 BLOCKING EVERY 8' MIN.; ¾" PLYWOOD SUBFLOOR+ SCHEDULED FLOOR FIN., ⅝" USG FIRECODE 'C' ON UNDERSIDE OF NEW JOISTS.

NEW 36"x80" SELF CLOSING ENTRY DOORS FOR BUILDING ACCESS/ EGRESS.

FAA (E)

3'-0"
6'-0" = 8 TREADS @ 9" EA.
3'-0"
3"
+/- 6'-4" VERIFY IN FIELD
4"
8'-0"
5"
5'-4"
6'-5"
2"